

Centrella® Smart+ Bed

Meets the changing needs of healthcare facilities and delivers elevated care through optimized patient safety, enhanced patient satisfaction and advanced caregiver-focused technology.



Standard Features Available on Base Model

OPTIMIZED PATIENT SAFETY

Enhanced 3-Mode Bed Exit with Silence and Auto Reset

Motion Activated Nightlight

One-button Patient Stand Assist

Advanced SlideGuard® Technology

Foley Position Limit & Drainage Bag Holder

Head Angle <30° Limit Control

Trendelenburg/Reverse Trendelenburg

Dampened Emergency CPR

Integrated Patient Helper Bracket

ENHANCED PATIENT SATISFACTION

Device Storage Area

Integrated Urinal Holders

FlexAfoot™ Powered Bed Extension

ADVANCED CAREGIVER-FOCUSED TECHNOLOGY

Graphical Caregiver Interface (GCI)® Touchscreen (right side)

Brake Not Set Alert

One-button Chair

Integrated Scale (kg/lbs)

Battery Backup

Four Corner Brake and Steer

Four Corner IV Pole Sockets

Integrated Restraint Holders

Lockout Controls

Built-in Line and Cord Management

WiFi Module

Smart Bed Ready (SideCom® Required)



Hillrom™

One Scalable Centrella® Platform

| BASE FRAME | PACKAGE 255 OPTION | PACKAGE 355 OPTION |
|--|---|---|
| Standard Features (listed on front page) | Advanced Patient Pendant | Centrella® max Powered Air Surface |
| Scalability | USB Charging | SafeView®+ System with IllumiGuide™ Siderail Handgrip |
| | Contact-Free, Continuous Monitoring Capable | Second Graphical Caregiver Interface (GCI)® Touchscreen |
| | Verbal Safety Prompts | |

TECHNICAL SPECIFICATIONS

| | |
|--|--|
| Overall frame width | 40" or 43" (Comfort Edition) (101.6 cm or 109.22 cm) |
| Overall frame length with foot extension | 86.7" - 98.7" (220 - 251 cm) (retracted - extended) |
| Bed height maximum | 32.5" (83 cm) |
| Bed height minimum | 14.5" (37 cm) |
| Head section inclination | 0° to 65° |
| Thigh section inclination | 0° to 25° |
| Foot section inclination | 0° to 50° |
| Trendelenburg/Reverse Trendelenburg position (max) | 15° |
| Caster size type | 5" (13 cm) Central Locking System |
| Safe working load | 650 lbs (295 kg) (includes patient weight, surface and accessories) |
| Patient weight range | 70 - 500 lbs (32 - 227 kg) |
| Centrella® core Surface 36"W x 76" - 88"L x 6"H (91 cm x 193-223 cm x 15 cm) | |
| Centrella® pro Surface 36" or 40"W x 76" - 88"L x 7"H (91.4 or 101.6 cm x 193-223 cm x 17.78 cm) | |
| Centrella® pro+ Surface 36" or 40"W x 76" - 88"L x 9"H (91.4 or 101.6 cm x 193-223 cm x 23 cm) | |
| Centrella® max Surface 36" or 40"W x 76" - 88"L x 8"H (91.4 or 101.6 cm x 193-223 cm x 20.32 cm) | |

IEC 60601-2-52 Compliance

hillrom.com

| A LA CARTE OPTIONS | |
|--|--|
| OPTIMIZED PATIENT SAFETY FEATURES | Centrella® max Powered Air Surface (includes Blower, Comfort Controls, Turn Assist and Focused Advanced Microclimate® Management Therapy) |
| | Centrella® pro+ surface (includes integrated blower, and Focused Advanced Microclimate® Management Therapy) |
| | Centrella® core Surface |
| | PATIENT SAFETY APPLICATIONS |
| | NaviCare® Patient Safety |
| | Contact-Free, Continuous Monitoring |
| ENHANCED PATIENT SATISFACTION FEATURES | WatchCare® Incontinence Management |
| | Comfort Edition 40" Width |
| | Patient Pendant (up to 2) |
| | Experience POD™ Device |
| | Active Nurse Call Button |
| ADVANCED CAREGIVER-FOCUSED TECHNOLOGY FEATURES | Universal TV and Lighting Controls |
| | SafeView®+ System (with IllumiGuide™ Siderail Handgrip) |
| | 5th Wheel Steering |
| | IntelliDrive® Powered Transport |
| | Second Graphical Caregiver Interface (GCI)® Touchscreen |
| | Accessory Outlet |
| | Additional Line Management |
| Obstacle Detect® System | |

Hill-Rom reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom makes is the express written warranty extended on the sale or rental of its products.

© 2021 Hill-Rom Services, Inc. ALL RIGHTS RESERVED. 203601 rev 7 28-JUN-2021 ENG - US